

Used machine available from Weinig UK
 Stock reference
WUK1395

-  Planers /Moulders
-  Ripsaws
-  Band Resaws
-  Scanner Systems
-  Crosscut Saws
-  Finger Jointing Lines
-  Tool Grinders/Tooling
-  Edgebanders
-  CNC Machining Centres
-  Horizontal Beam Saws
-  Vertical Panel Saw

Machine model:	Powermat 500-018	Serial number E. number	111.196
Availability:	c. April 2019	Year of Manu:	2008
Warranty offered:	6 months parts and labour		
Condition of sale:	Cleaned, checked and serviced		
Installation:	Installation included		
SALES PRICE: £54,950.00 + vat (subject to prior sale includes HIAB vehicle delivery to site UK mainland)			

Very well specified 6 head HSK moulder ideal for a milling application.




















Michael Weinig (UK) Limited









5 Blacklands Way, Abingdon Business Park, Abingdon, Oxon OX14 1DY. Tel: (01235) 557600. Website: www.weinig.com
 Sales and Accounts: Email: sales@weinig.co.uk. Servicing and Spares: Email: service@weinig.co.uk


Co. Reg. No. 1617754. Registered Office Address: 5 Blacklands Way, Abingdon Business Park, Abingdon, Oxon OX14 1DY.
 Vat Reg. No. GB 348 5661 25.

Outline Machine Specification

-  Powermat 500-018 6 head throughfeed moulder
-  Working width 20 – 230 mm
-  Working thickness 8 – 120 mm
-  1st bottom spindle HSK, 7.5kW (10 hp) and 8,000 rpm
-  Right spindle HSK, 7.5 kW (10 hp) and 8,000 rpm
-  Left spindle HSK, 7.5 kW (10 hp) and 8,000 rpm
-  1st top spindle HSK, 11 kW (15 hp) and 8,000 rpm
-  2nd top spindle HSK, 11 kW (15 hp) and 8,000 rpm
-  2nd bottom spindle HSK, 11 kW (15 hp) and 8,000 rpm

-  Pressure shoe in front of left toolholder incl 2 spring mounted pressure rollers
-  Vario hoods to both top spindles
-  Wooden table plate under 2nd top head
-  Guide for exchangeable profiles after 2nd top head
-  Feed motor 5 kW for 5 – 30 m/min
-  Setting range of feed roller opposite left spindle 35 mm with extension to 150 mm
-  Prepared for connection to infeed handling
-  Separate switch cabinet

-  Short infeed table 1.05 m with 2 driven rollers above the table and 1 serrated roller in table
-  Marathon Coating to tables and fences
-  Manual Waxillit pump
-  Driven roller in machine bed and at outfeed
-  PowerCom setting system
-  CNC radial positioning to left, both tops and feedbeam
-  Improved heavy duty sound enclosure
-  Anti-kickback device

-  Photos below are of machine before and during refurb







